


CERA

THE RIBBON G50 WAX IS A VERY FLEXIBLE PRODUCT ATTENDING A BIG VARIETY OF APPLICATIONS FOR PRINTING. IT IS USED TO BARCODE PRINTING AND VARIABLE INFORMATION ON PAPER AND ADHESIVE LABELS.

IT HAS A GREAT QUALITY PRINTING DUE THE FORMULATION AND COMPOSITION OF THE PRODUCT.

IT IS POSSIBLE TO USE IN SOME SYNTHETIC MATERIALS LIKE POLYETHYLENE AND POLYPROPYLENE, BESIDE THE MATT, GLOSSY AND TRANS THERMAL APPLICATIONS.






▶ HIGH RESOLUTION WITH LOW TEMPERATURE

- **▶** HIGH DENSITY PRINTING
- **▶** ANTISTATIC TREATMENT

SPECIFICATIONS	
COLOR	BLACK
POLIESTER FILM THICKNESS	4.5 μM
SILICONE COATING FILM THICKNESS	0.030 ± 0.005 G/M ²
INK COATING FILM THICKNESS	3.1 ± 0.2 G/M ²
INK FUSION POINT	73°C
PRINT SPEED	6 IPS
APPLICATIONS LABELS	LAMINATED PAPER (GLOSSY)
	NON LAMINATED PAPER (MATTE)
	TRANSTHERM PAPER
	SIMILAR PAPER







EXAMPLES OF APPLICATIONS

